


**5500 L TANK FOR CLEAN NON-DRINKING WATER WITH INTERNAL DRAIN
OR SUPPLY PUMP**

- **MATERIAL:** black rotomoulded polyethylene with UV protection.
- **INTERNAL DISCHARGE PUMP:** submerged pump, motor 1.1 KW single-phase 230 V 50Hz. 5 AMP. With single-phase earth, flow 2.9 m³/h. at 3 BARS
- **FUSE BOX:** 10 AMP circuit breaker.
- **ELECTRICAL CONNECTION:** built-in 16 AMP plug.
- **TANK CONTROL BOX:** pressure switch and expansion bubble set at 3-4 BARS pressure.
- **DRAINAGE SYSTEM TO MINIMUM 400 L.:**
Automatic safety shutoff with float so pump switches off when water volume reaches a minimum of 400 litres.
- **WATER OUTLET:** with manual valve or supply tap, 1" female threaded outlet connection.
- **WATER INLET:** with mesh filter, internal water entry shutoff float and 1" male threaded inlet connection.
- **POWER LINE (TO BE SUPPLIED ONSITE BY THE CLIENT):**
3G 1.5 mm diameter power line, 16 AMP/ 230 V. single-phase socket with earth connected.

**1" WATER
OUTLET****1" WATER
INLET****APPROXIMATE DIMENSIONS:****2500 X 2000 X 2400 MM. HEIGHT, CLEANOUT +- Ø 500 MM.****APPROX. CAPACITY 5500 LITRES***All information is subject to change without prior notice.*